

CARE INSTRUCTIONS

Care instructions for your artego kitchen!



Dear customer, so that you can enjoy your new artego kitchen for a long time, we would like to give you a few tips on care below.

The high-quality surfaces of an artego kitchen are easy to clean. To maintain the high value of your new kitchen for years you should care for it regularly, but above all properly. Please observe the following care instructions.

The following applies to all surfaces

Remove any soiling as soon as possible. Cleaning agents are then often not necessary. The best way with lukewarm water and a soft, damp cloth. Then rub the surfaces dry. Clean If necessary, only clean the surfaces with standard household water-soluble cleaning agents or kitchen cleaners. Do not use harsh liquid cleaners or abrasive cleaning agents! or abrasive cleaning agents! Polishes, waxes and solvents are also unsuitable for cleaning kitchen surfaces and do more

Vapour and heat

Ensure adequate ventilation when cooking. Ensure that any vapour produced does not condense on the furniture. Always use the extractor fan at the appropriate power level! Do not open the dishwasher until approx. 20 minutes after the programme has finished so that the steam can condense in the appliance

Care instructions for lacquered fronts

The surface of lacquered fronts consists of several layers of lacquer. It is protected by the application of a special lacquer that is highly resistant and abrasion-proof. Please clean and maintain only with a soft, clean cloth (no microfibre cloth!) and with standard household water-soluble cleaning agents. Do not use any aggressive or abrasive agents, polishes, waxes or steam cleaners. Under no circumstances should you use glass cleaners, as these contain solvent-based substances! If mineral or even metallic dust is picked up during cleaning, the cleaning agentsmust be permanentlyrinsed out so that the dust particles cannot leave any traces on the surface. Microscopic traces of use may occur. These are more or less noticeable depending on the colour and light. They do not represent a reduction in

Care instructions for plastic fronts

These are high-quality and hard-wearing fronts with plasticcoated surfaces. These surfaces should only be cleaned with normal household water-soluble cleaning agents or kitchen cleaners. The best way to do this is with lukewarm water and a

Warranty claims are void if the care instructions are not followed. Delivery possibilities, changes, errors and colour deviations withheld.

In the interests of sustainability, all fittings on our furniture are designed so that they are easy to dismantle and the carcass and all wooden parts can be recycled in accordance with recycling regulations.

harm than good. Follow the manufacturer's instructions for microfibre cloths, as these have different surface structures and can cause damage to the fronts. Please do not use steam cleaners. This leads to swelling and destroys the furniture. Ensure that the optimum humidity of your kitchen is between 40% - 65% (relative humidity). Short-term over- or underruns in the range of 2 - 3 days have no negative effects.

(see the appliance manufacturer's operating instructions). Do not allow steam, water and heat from electrical appliances such as microwave, coffee machine, kettle or egg boiler directly onto the furniture parts, as this can cause swelling. Damage of this kind does not constitute grounds for complaint.

the utility value but, as with all surfaces on cars, glasses or other furniture surfaces, they cannot be avoided in the long term. Such traces of use do not constitute grounds for complaint. To ensure that the fronts are not damaged during processing or transport, they are covered with a protective film. This film should only be removed in the final assembly step. After the protective film has been removed, it may still the familiar "paint odour" for a limited period of time. This will steadily less. When cured, the surface is very resistant. Depending on climatic conditions, final curing may take a few days after the protective film has been removed. Nevertheless, the lacquer surface must be handled with care during subsequent use.

soft, damp cloth. Then rub dry the surfaces afterwards. Do not use any aggressive or abrasive agents, vinegar or nitro cleaners, hard sponges or steam cleaners!



☑ www.artego-kuechen.de
 ⓓ info@artego-kuechen.de

☆ 05734/920-0
₩ 05734/920-110

